


CHB Series

磁滯式煞車器 Hysteresis Brake




型號 MODEL		CHB0S2AA	CHB0S7AA	CHB1S4AA	CHB2S5AA *	CHB3S5AA	CHB010AA	CHB020AA
額定扭力 Rated torque (Nm)		0.02	0.07	0.14	0.26	0.35	1.0	1.75
電壓 Voltage (V)		24						
電流 Current (A)		0.14	0.13	0.2	0.23	0.25	0.25	0.25
電力 Power [24V] (W)		3.3	3.2	4.8	5.5	6	6	6
慣性矩 Moment of inertia(J) (kgcm ²)		4.3x10 ⁻³	4.4x10 ⁻²	4.55x10 ⁻²	9.7x10 ⁻²	0.17	1.1	3.45
容許滑動功率 Heat Dissipation (W)		5.5	21	30	34	40	58	100
外 型 尺 寸 Exterior dimensions	D1	31.8	45.7	50	54.74(2.155")	60	92	112.7
	D2	10	14	14	15.875(0.625")	17	22	28
	d(h7)	3	5	5	6.35(0.250")	7	10	12
	D4	-	4.3	4.3	5.71(0.225")	6.3	9	-
	D5	19	19	21	23.01(0.906")	25	38	45
	L1	2	2.4	1.8	2.38(0.094")	2	2.5	3.9
	L2	0.25	0.6	0.6	0.635(0.025")	0.9	1	1
	L3	18.7	20.7	23.6	31.75(1.25")	39.7	39.1	50.4
	L4	42.2	52.6	55.8	76.2(3.0")	76.6	100	123.1
	L5	8	12.3	13	14.3(0.56")	15.3	25	27
	L6	23.6	25.5	27.3	42.93(1.69")	43	51.4	64.2
	L7	8.6	12.4	13.7	16(0.63")	16.3	21.1	28
	L8	-	9.5	9.5	9.525(0.375")	10	16	-
	L9	3-M2.5×4	3-M2.5×5	M3×6	#6-32x6L(0.25" L)	3-M4×10	3-M4×10	3-M5×12
	W	-	-	-	-	-	-	4
	T	-	-	-	-	-	-	13.5
重量 Weight (kg)	0.1	0.23	0.33	0.48	0.8	1.85	3.5	

特性 Special Features

【所容許的連續滑動扭力特性(自然冷卻時)】

Allowable Sustained torque levels (natural cooling)



【標準扭力特性】 (代表範例)

Torque v.s Input current (reference only)

